



THR 型新型气体腰轮流量计

产品概述

THR

EN12480 OIML R137

主要优势

- 4.0
-
-
-
- 4G Cat1 NFC BTE
- +
-

技术规格

| | mm/inch | (MPa) | | (m ³ /h) | (m ³ /h) | (m ³ /h) | Q _{max} (kPa) | m ³ | m ³ |
|------------|------------------------|-------|----------|---------------------|---------------------|---------------------|---------------------------|------------------------|----------------|
| THR-G6 | 20($\frac{3}{4}$ ") | 1.6 | 40:1 | 0.25 10 | 0.03 | 0.02 | 0.13 | 9× 10 ⁵ | 0.01 |
| THR-G10 | 25(1") | | 40:1 | 0.4 16 | 0.03 | 0.02 | 0.08 | 1.78× 10 ⁴ | 0.1 |
| THR-G16 | 32(1 $\frac{1}{4}$ ") | | 50:1 | 0.5 25 | 0.08 | 0.06 | 0.14 | 2.106× 10 ⁴ | |
| | 40(1 $\frac{1}{2}$ ") | | 50:1 | 0.5 25 | 0.08 | 0.06 | 0.12 | 2.106× 10 ⁴ | |
| | 50(2") | | 50:1 | 0.5 25 | 0.08 | 0.06 | 0.15 | 2.106× 10 ⁴ | |
| THR-G25 | 40(1 $\frac{1}{2}$ ") | | 80:1 | 0.5 40 | 0.06 | 0.05 | 0.15 | 2.838× 10 ⁴ | |
| | 50(2") | | 80:1 | 0.5 40 | 0.06 | 0.05 | 0.13 | 2.838× 10 ⁴ | |
| THR-G40 | 40(1 $\frac{1}{2}$ ") | | 130:1 | 0.5 65 | 0.06 | 0.04 | 0.35 | 5.676× 10 ⁴ | |
| | 50(2") | | 130:1 | 0.5 65 | 0.06 | 0.04 | 0.24 | 5.676× 10 ⁴ | |
| THR-G65 | 50(2") | | 200:1 | 0.5 100 | 0.06 | 0.05 | 0.42 | 7.107× 10 ⁴ | |
| THR-G100 | 80(3") | | 250:1 | 0.65 160 | 0.04 | 0.03 | 0.42 | 1.053× 10 ³ | |
| THR-G160-3 | 80(3") | | 160:1 | 1.6 250 | 0.15 | 0.10 | 0.52 | 2.785× 10 ³ | |
| THR-G160-4 | 100(4") | | 160:1 | 1.6 250 | 0.15 | 0.10 | 0.39 | 2.785× 10 ³ | |
| THR-G250 | 100(4") | | 200:1 | 2.0 400 | 0.10 | 0.06 | 0.51 | 4.211× 10 ³ | |
| THR-G400-4 | 100(4") | | 260:1 | 2.5 650 | 0.30 | 0.20 | 0.70 | 5.661× 10 ³ | |
| THR-G400-6 | 150(6") | | 100:1 | 6.5 650 | 0.70 | 0.50 | 0.43 | 1.049× 10 ² | |
| THR-G650 | 150(6") | 160:1 | 6.5 1000 | 0.80 | 0.60 | 0.47 | 1.574× 10 ² | | |
| THR-G1000 | 200(8") | 160:1 | 10 1600 | 1.20 | 0.90 | 0.65 | 1.971× 10 ² | 10.0 | |

1.2kg/m³

天信仪表集团有限公司

A: 浙江省温州市苍南县工业园区花莲路 198 号
T: 0577-6885 6655

W: www.tancy.com
E: tancy@tancy.com

